

Page 1/7

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: VINYFLEX ACRYLIC CEMENT PAINT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Acrylic Emulsion Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

VECHRO S.A. Liosion 302 111 45 ATHENS GREECE quality@vechro.gr info@vechro.gr www.vechro.gr

· Further information obtainable from:

Regulatory Division quality@vechro.gr

• 1.4 Emergency telephone number: Poison control center: +302107793777

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

 The product is not classified, according to the GB CLP regulation.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

Contains a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1), 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 2)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

(Contd. of p				
Dangerous compone	ents:			
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide	10.0%		
CAS: 57-55-6	Propylene glycol	1.1%		
EINECS: 200-338-0	♠ Acute Tox. 4, H302			
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; ♠ Aquatic Acute 1, H400; ♠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	0.007%		
	a mixture of: 5-chloro-2-methyl-2 H -isothiazol-3-one [EC No 247-500-7] and 2-methyl-2 H -isothiazol-3-one [EC No 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1B, H314; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	0.001%		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out into the fresh air.
- · After inhalation: Supply fresh air.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Seek immediate medical advice.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Dry sand

Water haze

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

(Contd. of page 2)

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep away from heat and direct sunlight.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from flammable substances.

· Further information about storage conditions:

Protect from exposure to the light.

Store under lock and key and out of the reach of children.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm

*total vapour and particulates **particulates

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Do not eat or drink while working.

Storing food in the working area is prohibited.

Wash hands before breaks and at the end of work.

- · Respiratory protection: well ventilated working area
- · Hand protection

The glove material has to be impermeable and resistant to the product.

Due to missing tests no recommendation to the glove material can be given for the product.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.


- · Not suitable are gloves made of the following materials: Natural rubber, NR
- · Eye/face protection Goggles recommended during refilling

(Contd. on page 4)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

· Body protection:



(Contd. of page 3)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state Colour: Fluid White

Odour: Weak, characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 100 °C (CAS: 7732-18-5 water, distilled, conductivity

or of similar purity)

· Flammability Not applicable.

Lower and upper explosion limit

Lower:

Vipper:
Not determined.
Not applicable.
Not applicable.
Not determined
Not determined
Not determined
Not determined
Not determined
Not determined.
Not determined.

· Viscosity:

• Kinematic viscosity
• Dynamic at 20 °C:

Not determined.
2,205 mPas

·Solubility

• water: Fully miscible.
• Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 23 hPa (CAS: 7732-18-5 water, distilled, conductivity

or of similar purity)

· Density and/or relative density

Density: Not determined.
Relative density Not determined.
Bulk density: 1-2 kg/m³
Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Liquid

 $\cdot \ Important \ information \ on \ protection \ of \ health \ and$

environment, and on safety.

· Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent content:

 · Organic solvents:
 1.2 %

 · Water:
 31.6 %

 · VOC (EC)
 1.17 %

 · Solids content:
 44.8 %

· Change in condition

· Evaporation rate Not determined.

 $\cdot \ \, \textbf{Information with regard to physical hazard classes} \\$

· Explosives Void

(Contd. on page 5)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

		(Contd. of page 4)
· Flammable gases	Void	
· Aerosols	Void	
· Oxidising gases	Void	
· Gases under pressure	Void	
· Flammable liquids	Void	
· Flammable solids	Void	
· Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
· Pyrophoric solids	Void	
· Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute to	oxicity		
· LD/LC	50 valu	nes relevant for classification:	
ATE (A	cute T	oxicity Estimates)	
Oral	LD50	181,818 mg/kg (rat)	
CAS: 13	3463-6	7-7 titanium dioxide	
Oral	LD50	>20,000 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rabbit)	
CAS: 5'	7-55-6	Propylene glycol	
Oral	LD50	2,000 mg/kg (rat)	
Dermal	LD50	20,800 mg/kg (rabbit)	
· 11.2 Inf	ormati	ion on other hazards	
· Endocr	· Endocrine disrupting properties		
None of	the ing	gredients is listed.	

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 6)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

(Contd. of page 5)

- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Minimize product wastage by estimating how much product you will need. Reuse when possible.

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR, IMDG, IATA	not regulated
· 14.2 UN proper shipping name · ADR, IMDG, IATA	not regulated
· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA · Class	not regulated
· 14.4 Packing group · ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to instruments	Not applicable.
· UN "Model Regulation":	not regulated

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 7)

Printing date 07.06.2022 Version number 2 Revision: 07.06.2022

Trade name: VINYFLEX ACRYLIC CEMENT PAINT

(Contd. of page 6)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Department issuing SDS: Regulatory Division

· Contact: quality@vechro.gr

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

GB